

SAMSUNG SSD 2.5" SATA 3.0Gb/s(SLC)

General					
	64GB	50GB	32GB	25GB	
Manufacturer	SAMSUNG				
Model	2.5" 64GB SATA SSD				
Interface	SATA 3.0Gb/s				
Performance					
Host Transfer Rate	300MB/sec				
Maximum Sequential Read Rate	100MB/s				
Maximum Sequential Write Rate	80MB/s				
Drive Capacity					
	64GB	50GB	32GB	25GB	
Unformatted Capacity	64GB	50GB	32GB	25GB	
User-Addressable Sectors	125,045,424	97,696,367	62,533,296	48,858,768	
Bytes per Sector	512	512	512	512	
Electrical					
Voltage	5V ±5%				
Power Consumption					
Read/Write	0.48W/0.46W				
Idle (DIPM Enabled)	0.2W				
Stanby (DIPM Enabled)	0.2W				
Sleep (DIPM Enabled)	0.2W				
Reliability					
S.M.A.R.T Support	Yes				
MTBF	2,000,000 Hours				
Preventive Maintenance	None required				
Environment					
Temperature					
Operating	0°C to 70°C				
Non-Operating	-55°C to 95°C				
Shock					
Operating	1500G, (@ 0.5msec half sine wave)				
Non-Operating	1500G, (@ 0.5msec half sine wave)				
Vibration	20G Peak, 10 ~ 2000Hz, (15mins/ Axis) x3 Axis				
Humidity	0°C to 55°C / 90~98% RH				
Physical					
	2.5"				
Width	69.85 ± 0.25mn				
Height	9.5 ± 0.2 mm				
Length	100.3 ± 0.2 mm				
Weight	73g				

Aug. 2008